FORM PTO-1390 ATTORNEY DOCKET NUMBER						
(RE+	(REV 12-2001) 3401-4035					
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US)				U.S. APPLICATION NO. (If known see 37 CFR 1.51		
		CONCERNING A FILI	10/070564			
INT	ERN	ATIONAL APPLICATION	PRIORITY DATE CLAIMED			
		00/02486 F INVENTION	8 September 2000 (08/09/2000)	10 September 1999 (10/09/1999)		
DE	VICE	E FOR ACQUIRING STER	EOSCOPIC IMAGES			
		ANT(S) FOR DO/EO/US COSTES				
-			ates Designated/Elected Office (DO/EO/US) the fol	ollowing items and other information:		
1.	\boxtimes	This is FIRST submission of iter	ms concerning a filing under 35 U S.C. 371.	ľ		
2.		This is SECOND or SUBSEQUE	ENT submission of items concerning a filing under	r 35 U.S.C. 371.		
3.	⊠	This express request to begin natibelow.	ional examination procedures (35 U S C. 371(f))	The submission must include items (5), (6), (9) and (21)		
4.	\boxtimes	The US has been elected by the e	expiration of 19 months from the priority date (Artic	cle 31).		
5.	\boxtimes	A copy of the International Appl	lication as filed (35 U.S.C. 371(c)(2))			
		is attached hereto (required only has been communicated by the	y if not communicated by the International Bureau)).		
			on was filed in the United States Receiving Office ((RO/US).		
6.	\boxtimes	An English translation of the Inte	ernational application as filed (35 U.S.C. 371(c)(2))).		
		 a.				
7.	\boxtimes	Amendments to the claims of the International Application under PCT Article 19 (35 U S.C 371(c)(3))				
	a. □ are attached hereto (required only if not communicated by the International Bureau). □ have been communicated by the International Bureau. □ have not been made; however, the time limit for making such amendments has NOT expired □ have not been made and will not be made.					
8.	⊠	An English translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).				
9.		An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).				
10.	10. An English translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).					
Items 11. to 20. below concern document(s) or information included.						
11.		An Information Disclosure States	ment under 37 CFR 1.97 and 1 98			
12.		An assignment document for rec	ording A separate cover sheet in compliance with	37 CFR 3 28 and 3.31 is included.		
13.	\boxtimes	A FIRST preliminary amendmen	nt.			
14.		A SECOND or SUBSEQUENT	preliminary amendment.			
15.		A substitute specification.				
16.		A change of power of attorney ar	nd/or address letter.			
17.		A computer-readable form of the	e sequence listing in accordance with PCT Rule 13t	ter 2 and 35 U S C. 1.821-1.825.		
18.		A second copy of the published i	international application under 35 U.S.C. 154(d)(4)).		
19.		A second copy of the English tra	anslation of the international application under 35 U	J.S.C 154(d)(4).		
20.	\boxtimes	Other items or Information:				
		Conv of International Search Res	nort dated November 9, 2000	,		

U.S. APPLICATION NO (1f known, see 37 C F R 1 51 INTERNATIONAL APPLICATION NO					ATTORNEY'S DOCKET NO	
10/07056 LPCT/FR00/02486					3401-4035	
21.		following fees are	CALCULATIONS	PTO USE ONLY		
	NATION	NAL FEE (37 CFR	1.492 (a) (1) - (5)			
		ational preliminary ex				
		nal search fee (37 CFI				
апи	Internation	nal Search Report not	prepared by the EFC	or JPO\$1,040.00		
Inte	rnational n	oreliminary examinati	on fee (37 CFR 1.48)	2) not paid to		
				EPO or JPO \$890.00		
-			port prepared as	210000000000000000000000000000000000000		
				2) not paid to USPTO		
but i	internation	al search fee (37 CFI	R 1.445(a)(2) paid to	USPTO\$740.00		
	1		° 'l' HODE	C C T C T T 1 400\		
		oreliminary examinati		O (37 CFR 1.482) 3 (1) - (4) \$710.00		
Dut :	an ciaims	aid not satisfy provisi	ons of PC1 Article 3	3 (1) - (4)\$/10.00		
Inte	rnational r	oreliminary examinati	on fee paid to USPT(O (37 CFR 1 482)	<u> </u>	-
and	all claims	satisfied provisions o	f PCT Article 33(1) -	· (4) \$100.00		
		•	1 /	()	\$890.00	
	ENTER	APPROPRIATE B	ASIC FEE AMOU	INT =	Ψ070.00	
		for furnishing the oat			\$	
months fi	rom the ea	rliest claimed priority	date (37 CFR 1.492)	(e)).	Ф	
CLA	IMS	NUMBER FILED	NUMBER EXTRA	RATE	\$	
Total clair	ms	7 - 20 =	0	X \$18.00	\$0	
Independe	ent claims	2 - 3 =	0	X \$84.00	\$0	
		DENT CLAIM(S) (if ap	l		\$	
MOLTIPL	LE DEPENI		·	+ \$280.00	D	
		TOTAL OI	F ABOVE CAL	LCULATIONS =	\$890.00	
		ing by small entity, if ap		ty Statement	\$	
must also	by filed (No	ote 37 CFR 1.9, 1.27, 1.2	<u>!8).</u>		J.	
				SUBTOTAL =	\$890.00	
		0.00 for furnishing the E est claimed priority date		than	\$	
			TOTAL NA	TIONAL FEE =	\$890.00	
Fee for rec	cording the	enclosed assignment (37 opropriate cover sheet (3	\$.			
accompan	ned by an ap	propriate cover sneet (3				
			TOTAL FE	EES ENCLOSED	\$890.00	
					Amount to be	\$
					refunded:	
		· · · · · · · · · · · · · · · · · · ·			charged	\$
a. A check in the amount of \$890 00 to cover the above fees is enclosed.						
b. Please charge my Deposit Account No. in the amount of \$ to cover the above fees.						
c. The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any						
overpayment to Deposit Account No. 13-4500, Order No. 3401-4035. A duplicate copy of this sheet is enclosed.						
d. Fees are to be charged to a credit card. WARNING: Information on this form may become public. Credit card information						
should not be included on this form. Provide credit card information and authorization on PTO-2038.						
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.						
SEND ALL CORRESPONDENCE TO: Date: March /, 2002						Laury
SEND ALL CORRESPONDENCE TO:						
MORGAN & FINNEGAN, L.L.P.						
345 Park		1.0052		Joseph A. Calvarus	0	
New York, NY 10154-0053 (212) 758-4800 Telephone						
	(212) 751-6849 Facsimile 28,287					
REGISTRATION NO					NO.	

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE (DO/EO/US)

Applicants

Vincent COSTES

International Application No.:

PCT/FR00/02486

5 U.S. Serial No.

To be assigned

U.S. Filing Date.

To be assigned

Group Art Unit

To be Assigned

Examiner

To be Assigned

For

10

20

DEVICE FOR ACQUIRING STEREOSCOPIC

IMAGES

PRELIMINARY AMENDMENT

Commissioner for Patents

Box PCT

15 Washington, D.C. 20231

Attention: DO/EO/US

SIR:

Preliminary to a substantive examination on the merits, please amend the above identified application as follows:

Please amend the Specification and Claims as follows:

IN THE SPECIFICATION

At page 1, after the third full paragraph and between lines 10 and 11, please

25 insert

-- Document FR 1 393 577 describes a collimator device

for infrared radiation. That device comprises:

- a parabolic primary mirror;

- a hyperbolic secondary mirror positioned between the primary mirror M1 and its focus;
- an elliptical tertiary mirror disposed relative to the
 primary mirror on its side opposite from its side on which the
 secondary mirror is disposed; and

5

15

20

- a detector positioned at the focus of the tertiary mirror.

Such a device serves to concentrate a light beam received by the primary mirror parallel to its optical axis onto the detector. –

10 At page 1, after the fourth full paragraph and between lines 23 and 24, please insert

device, comprising a concave spherical primary mirror, a convex spherical secondary mirror positioned on the optical axis of the primary mirror, the primary mirror suitable for passing the light beams reflected by the secondary mirror so as to enable them to reach a catadioptric lens. Such a device enables an incident beam parallel to the optical axis to be split into two beams, these two beams corresponding respectively to the portions of the beam that pass on either side of two secondary half-mirrors.

Document EP 0 655 636 describes an aiming eyepiece device having an inlet pupil, a primary mirror, a secondary mirror, and a refractive lens. The elements are disposed in such

10070564 C730CE

PATENT

Docket No. 3401-4035

a manner as to transmit an image of the refractive lens towards the inlet pupil. –

At page 1, after the seventh full paragraph and between lines 35 and 36, please insert

Thus, the device proposed by the invention is an observation device according to claim 1. –

At page 1 and extending to page 2 delete the paragraph beginning "Thus, the device proposed by the invention is ..." and ending on page 2, line 19 with "directions onto image acquisition means."

IN THE CLAIMS

10

15

20

1. (twice amended) An observation device comprising a primary mirror that is parabolic or nearly parabolic, secondary reflection means situated between the primary mirror and its focus, and tertiary reflection means which are disposed relative to the primary mirror on its side opposite from the side on which the secondary reflection means are disposed, the secondary reflection means reflecting light beams that are received by the primary mirror, the primary mirror being suitable for passing the light beams reflected in this way so as to enable them to reach the tertiary reflection means, the device being characterized in that it further comprises image acquisition means, and in that in order to acquire stereoscopic images, the secondary reflection means comprise a mirror situated on the optical axis of the primary mirror which reflects along two directions that are distinct from the optical axis of the primary mirror, the light beams that are received by the primary mirror along two directions of incidence that are also distinct from its optical axis, the tertiary reflection

10070564.073002

PATENT

Docket No. 3401-4035

means comprising means for focusing the light beams they receive along said two directions onto image acquisition means.

2. (twice amended) A device according to claim 1, characterized in that the secondary mirror is adapted to reflect symmetrically about the optical axis the optical beams which reach the primary mirror along said two directions of incidence that are symmetrically about the optical axis.

5

20

- 3. (amended) A device according to claim 2, characterized in that the tertiary reflection means comprise two plane mirrors placed symmetrically on either side of the direction of the optical axis of the primary mirror, together with two concave mirrors also disposed symmetrically about said direction, the plane mirrors reflecting onto the concave mirrors the light beams which come from the secondary mirror along the two directions that are distinct from the direction of the optical axis of the primary mirror, the concave mirrors reflecting the beams they receive so as to focus them on the acquisition means.
 - 4. (amended) A device according to claim 2, characterized in that the tertiary reflection means comprise two concave mirrors which are disposed symmetrically on either side of the direction of the optical axis of the primary mirror and which reflect the light beams which arrive from the secondary mirror along the two directions distinct from the direction of the optical axis of the primary mirror, together with a plane mirror which is common to both paths and which is centered on the direction of the optical axis, extending perpendicularly to said direction, said plane mirror

10070564.075002

PATENT

Docket No. 3401-4035

reflecting the beams it receives onto the acquisition means situated on a focal plane common to both paths.

- 5. (amended) A device according to claim 2, characterized in that the primary mirror includes a central hole through which the secondary mirror reflects light.
 - 6. (amended) A device according to claim 5, characterized in that the secondary mirror focuses two intermediate images at the level of the primary mirror, with the two light beams they reflect corresponding to the two observed directions of incidence.
- 7. (amended) A stereoscopic observation system comprising a satellite and stereoscopic image acquisition means, characterized in that said means comprise a device according to any preceding claim.

15

20

10

5

REMARKS

The above amendments have been made to incorporate the amendments made in the International Application PCT/FR00/02486 and to conform with United States claim drafting criteria, and eliminate character references. No new matter has been added to the application as a result of this amendment.

PATENT

Docket No. 3401-4035

The Commissioner is hereby authorized to charge any additional fees which may be required for this amendment, or credit any overpayment to Deposit Account No. 13-4500, Order No. 3401-4035.

Respectfully submitted,

MORGAN & FINNEGAN, L.L.P.

5

10

Dated: March

, 2002

MORGAN & FINNEGAN, L.L.P. 345 Park Avenue New York, New York 10154 Tel. No. (212)758-4800 Fax No. (212)751-6849 Registration No. 28,287

PATENT Docket No. 3401-4035

The Commissioner is hereby authorized to charge any additional fees which may be required for this amendment, or credit any overpayment to Deposit Account No. 13-4500, Order No. 3401-4035.

Respectfully submitted,

MORGAN & FINNEGAN, L.L.P.

Dated: March

5

, 2002

MORGAN & FINNEGAN, L.L.P.

10 345 Park Avenue New York, New York 10154 Tel. No. (212)758-4800 Fax No. (212)751-6849

APPENDIX A (Claim with changes shown)

1[/]. (twice amended) An observation device comprising a primary mirror

5

10

15

20

25

[(1)] that is parabolic or nearly parabolic, secondary reflection means [(2)] situated between the primary mirror [(1)] and its focus, and tertiary reflection means [(4a, 4b; 5a, 5b; 7a, 7b; 8)] which are disposed relative to the primary mirror [(1)] on its side opposite from the side on which the secondary reflection means [(2)] are disposed, the secondary reflection means [(2)] reflecting light beams that are received by the primary mirror [(1)], the primary mirror [(1)] being suitable for passing the light beams reflected in this way so as to enable them to reach the tertiary reflection means [(4a, 4b; 5a, 5b; 7a, 7b; 8)], the device being characterized in that [in order to acquire stereoscopic images, the secondary reflection means comprise a mirror (2)] it further comprises image acquisition means [(6a, 6b; 9)], and in that in order to acquire stereoscopic images, the secondary reflection means comprise a mirror [(2] situated

received by the primary mirror [(1)] along two [given] directions of incidence that are also distinct from its optical axis, the tertiary reflection means [(4a, 4b; 5a, 5b; 7a, 7b; 8)] comprising means for focusing the light beams they receive along said two directions onto image acquisition means [(6a, 6b; 9)].

on the optical axis of the primary mirror [(1)] which reflects along two directions that

are distinct from the optical axis of the primary mirror [(1)], the light beams that are

2[/]. (twice amended) A device according to claim 1, characterized in that the [two directions of incidence that it observes are symmetrical about the optical axis, and in that the light] secondary mirror [(2)] is adapted to reflect symmetrically about

the optical axis the optical beams which reach the primary mirror [(1)] along said two directions of incidence that are [reflected by the secondary mirror (2)] symmetrically about the optical axis.

5

3[/]. (amended) A device according to claim 2, characterized in that the tertiary reflection means comprise two plane mirrors [(4a, 4b)] placed symmetrically on either side of the direction of the optical axis of the primary mirror [(1)], together with two concave mirrors [(5a, 5b)] also disposed symmetrically about said direction, the plane mirrors [(4a, 4b)] reflecting onto the concave mirrors [(5a, 5b)] the light beams which come from the secondary mirror [(2)] along the two directions that are distinct from the direction of the optical axis of the primary mirror [(1)], the concave mirrors reflecting the beams they receive so as to focus them on the acquisition means [(6a, 6b)].

15

20

10

4[/]. (amended) A device according to claim 2, characterized in that the tertiary reflection means comprise two concave mirrors [(7a, 7b)] which are disposed symmetrically on either side of the direction of the optical axis of the primary mirror [(1)] and which reflect the light beams which arrive from the secondary mirror [(2)] along the two directions distinct from the direction of the optical axis of the primary mirror [(1)], together with a plane mirror [(8)] which is common to both paths and which is centered on the direction of the optical axis, extending perpendicularly to said direction, said plane mirror [(8)] reflecting the beams it receives onto the acquisition means situated on a focal plane common to both paths.

5[/]. (amended) A device according to claim 2, characterized in that the primary mirror [(1)] includes a central hole through which the secondary mirror [(2)] reflects light.

6[/]. (amended) A device according to claim 5, characterized in that the secondary mirror [(2)] focuses two intermediate images at the level of the primary mirror [(1)], with the two light beams they reflect corresponding to the two observed directions of incidence.

5

7[/]. (amended) A stereoscopic observation system comprising a satellite and stereoscopic image acquisition means, characterized in that said means comprise a device according to any preceding claim.

A DEVICE FOR ACQUIRING STEREOSCOPIC IMAGES

. 5

10

15

20

25

30

35

The present invention relates to a device for acquiring stereoscopic images.

It is recalled that stereoscopic images are obtained by viewing the same scene from two different angles of incidence.

An object of the invention is to propose a device for acquiring stereoscopic images that is particularly simple, compact, and adapted to very good angular resolution.

Document FR 1 393 577 describes a collimator device for infrared radiation. That device comprises:

- a parabolic primary mirror;
- a hyperbolic secondary mirror positioned between the primary mirror M1 and its focus;
- an elliptical tertiary mirror disposed relative to the primary mirror on its side opposite from its side on which the secondary mirror is disposed; and
- a detector positioned at the focus of the tertiary mirror.

Such a device serves to concentrate a light beam received by the primary mirror parallel to its optical axis onto the detector.

DE 4 307 831 discloses binocular telescopic structures making it possible to observe remote scenes and comprising:

- a parabolic mirror;
- secondary mirrors situated on either side of the optical axis of the primary mirror, between said primary mirror and its focal plane; and
- tertiary reflection means disposed relative to the primary mirror on its side opposite from the side on which the secondary mirror is disposed, and in which the primary mirror is adapted to pass the light beams reflected by the secondary mirrors so as to enable them to reach the tertiary reflection means.

Document UK 2 158 261 describes a similar optical device, comprising a concave spherical primary mirror, a convex spherical secondary mirror positioned on the optical axis of the primary mirror, the primary mirror being suitable for passing the light beams reflected by the secondary mirror so as to enable them to reach a catadioptric lens. Such a device enables an incident beam parallel to the optical axis to be split into two beams, these two beams corresponding respectively to the portions of the beam that pass on either side of two secondary half-mirrors.

5

10

15

20

25

30

35

Document EP 0 655 636 describes an aiming eyepiece device having an inlet pupil, a primary mirror, a secondary mirror, and a refractive lens. The elements are disposed in such a manner as to transmit an image of the refractive lens towards the inlet pupil.

Such a telescope is intended for observing objects that are very far away (an application to astronomy, for example) and is not suitable in any way for acquiring stereoscopic images.

The invention proposes an optical device which makes it possible to observe the same scene with different angles of incidence.

In particular, the device proposed by the invention is advantageously applicable in acquiring a stereoscopic image by means of a satellite moving over the earth and observing the same scene at two different instants, and thus at two different angles.

Thus, the device proposed by the invention is an observation device according to claim 1.

The invention advantageously also has the various following characteristics, taken singly or in any technically feasible combination:

- the two directions of incidence that it observes are symmetrical about the optical axis, and the light beams which reach the primary mirror along said two

May controlled directions of incidence are reflected by the secondary mirror symmetrically about the optical axis;

5

10

- the tertiary reflection means comprise two plane mirrors placed symmetrically on either side of the direction of the optical axis of the primary mirror, together with two concave mirrors also disposed symmetrically about said direction, the plane mirrors reflecting onto the concave mirrors the light beams which come from the secondary mirror along the two directions that are distinct from the direction of the optical axis of the primary mirror, the concave mirrors reflecting the

beams they receive so as to focus them on the acquisition means;

- the tertiary reflection means comprise two concave mirrors which are disposed symmetrically on either side of the direction of the optical axis of the primary mirror and which reflect the light beams which arrive from the secondary mirror along the two directions distinct from the direction of the optical axis of the primary mirror, together with a plane mirror which is common to both paths and which is centered on the direction of the optical axis, extending perpendicularly to said direction, said plane mirror reflecting the beams it receives onto the acquisition means situated on a focal plane common to both paths;

5

10

15

20

25

30

35

- the primary mirror includes a central hole through which the secondary mirror reflects light; and
- the secondary mirror focuses two intermediate images at the level of the primary mirror, with the two light beams they reflect corresponding to the two observed directions of incidence.

Other characteristics and advantages of the invention appear further from the following description. This description is purely illustrative and non-limiting. It should be read with reference to the accompanying drawings, in which:

- Figure 1 shows a device constituting one possible embodiment of the invention;
- Figure 2 shows a device constituting another possible embodiment of the invention;
- Figure 3 shows a device constituting a third possible embodiment of the invention; and
- Figure 4 is a diagrammatic perspective view of the Figure 3 device.

The device shown in Figure 1 comprises a primary mirror 1 of conical shape close to that of a parabola, together with a convex mirror 2 which is placed on the optical axis of said primary mirror 1 and which

intercepts the beams reflected by said parabolic mirror 1 before they reach its focus.

The primary mirror 1 is pieced by a central hole passing intermediate images 3a and 3b which are disposed symmetrically on either side of its center.

5

10

15

20

25

30

35

The primary and secondary mirrors 1 and 2 are dimensioned in such a manner that the beams which are incident on said primary mirror 1 with respective angles $\theta 1$ and $-\theta 1$ relative to the optical axis of said primary mirror 1 are focused respectively on the central hole.

The device also has two plane mirrors 4a, 4b which are disposed symmetrically about the optical axis of the primary mirror 1, being situated on the side of said primary mirror 1 that is opposite from the side where the secondary mirror 2 is situated.

The two plane mirrors 4a and 4b lie respectively on the paths of the beams which, after being reflected by the convex mirror 2, pass through the mirror 1 via the intermediate images 3a and 3b.

These plane mirrors 4a and 4b reflect the beams they receive from the images 3a and 3b onto two concave mirrors 5a and 5b which are conical and which reflect the beams they receive onto two focus planes 6a and 6b where charge coupled detector strips or matrices are located, for example.

As will have been understood, such a device makes it possible in simple manner to acquire two images which correspond to the same scene as viewed at two different angles of incidence.

Numerous variants of the embodiment shown in Figure 1 can be envisaged.

In particular, depending on the shape and the dimensions of the volume in which the rear portion of the telescope is to be housed, it is naturally possible to act on the orientations of the plane mirrors 4a and 4b and on the orientations of the concave mirrors 5a and 5b.

Thus, Figure 2 shows a situation in which the focus planes 6a and 6b are parallel to the optical axis of the primary mirror 1 and are interposed between said optical axis and the concave mirrors 5a and 5b.

5

10

15

20

25

30

to both paths.

In another variant, as shown in Figures 3 and 4, the beams coming out from the central hole and serving to pass the intermediate images 3a and 3b can be reflected by conical concave mirrors 7a and 7b placed symmetrically on either side of the axis of the primary mirror 1. These concave mirrors 7a and 7b focus the beams they receive by reflecting them onto a plane mirror 8 that is common to both reflection paths. This plane mirror 8 is centered on the direction of the optical axis of the primary mirror 1 and is perpendicular to said direction. It reflects the beams onto a focus plane 9 that is common

A strip or a matrix of charge coupled devices that is common to both paths can be situated in the focus plane 9, for example.

A device of the types described above is advantageously used on board a satellite orbiting the earth, so as to observe the same scene at two different instants, and thus with different aiming directions.

By way of example, these aiming directions can be angularly separated by an angle lying in the range 2° to 10° .

The device proposed by the invention enables the satellite to acquire images in those two aiming directions, i.e. without any need to alter the attitude of the satellite or the direction in which the observation device points relative to the satellite.

CLAIMS

5

10

15

20

25

30

1/ An observation device comprising a primary mirror (1) that is parabolic or nearly parabolic, secondary reflection means (2) situated between the primary mirror (1) and its focus, and tertiary reflection means (4a, 4b; 5a, 5b; 7a, 7b; 8) which are disposed relative to the primary mirror (1) on its side opposite from the side on which the secondary reflection means (2) are disposed, the secondary reflection means (2) reflecting light beams that are received by the primary mirror (1), the primary mirror (1) being suitable for passing the light beams reflected in this way so as to enable them to reach the tertiary reflection means (4a, 4b; 5a, 5b; 7a, 7b; 8), the device being characterized in that it further comprises image acquisition means (6a, 6b; 9), and in that in order to acquire stereoscopic images, the secondary reflection means comprise a mirror (2) situated on the optical axis of the primary mirror (1) which reflects along two directions that are distinct from the optical axis of the primary mirror (1), the light beams that are received by the primary mirror (1) along two directions of incidence that are also distinct from its optical axis, the tertiary reflection means (4a, 4b; 5a, 5b; 7a, 7b; 8) comprising means for focusing the light beams they receive along said two directions onto the image acquisition means (6a, 6b; 9).

2/ A device according to claim 1, characterized in that the secondary mirror (2) is adapted to reflect symmetrically about the optical axis the optical beams which reach the primary mirror (1) along two directions of incidence that are symmetrical about the optical axis.

3/ A device according to claim 2, characterized in that
the tertiary reflection means comprise two plane mirrors
(4a, 4b) placed symmetrically on either side of the
direction of the optical axis of the primary mirror (1),
together with two concave mirrors (5a, 5b) also disposed


symmetrically about said direction, the plane mirrors (4a, 4b) reflecting onto the concave mirrors (5a, 5b) the light beams which come from the secondary mirror (2) along the two directions that are distinct from the direction of the optical axis of the primary mirror (1), the concave mirrors reflecting the beams they receive so as to focus them on the acquisition means (6a, 6b).

5

25

30

- 4/ A device according to claim 2, characterized in that the tertiary reflection means comprise two concave 10 mirrors (7a, 7b) which are disposed symmetrically on either side of the direction of the optical axis of the primary mirror (1) and which reflect the light beams which arrive from the secondary mirror (2) along the two 15 directions distinct from the direction of the optical axis of the primary mirror (1), together with a plane mirror (8) which is common to both paths and which is centered on the direction of the optical axis, extending perpendicularly to said direction, said plane mirror (8) 20 reflecting the beams it receives onto the acquisition means situated on a focal plane common to both paths.
 - 5/ A device according to claim 2, characterized in that the primary mirror (1) includes a central hole through which the secondary mirror (2) reflects light.
 - 6/ A device according to claim 5, characterized in that the secondary mirror (2) focuses two intermediate images at the level of the primary mirror (1), with the two light beams they reflect corresponding to the two observed directions of incidence.
- 7/ A stereoscopic observation system comprising a satellite and stereoscopic image acquisition means, characterized in that said means comprise a device according to any preceding claim.



(19) Organisation Mondiale de la Propriété Intellectuelle

Bureau international



(43) Date de la publication internationale 22 mars 2001 (22.03.2001)

PCT

(10) Numéro de publication internationale WO 01/20385 A1

- (51) Classification internationale des brevets⁷: G02B 17/06, 21/22
- (21) Numéro de la demande internationale:

PCT/FR00/02486

(22) Date de dépôt international:

8 septembre 2000 (08.09.2000)

(25) Langue de dépôt:

français

(26) Langue de publication:

français

(30) Données relatives à la priorité:


99/11355

10 septembre 1999 (10 09 1999) FR

- (71) Déposant (pour tous les États désignés sauf US): CENTRE NATIONAL D'ETUDES SPATIALES [FR/FR]; 2, place Maurice Quentin, F-75001 Paris (FR).
- (72) Inventeur; et
- (75) Inventeur/Déposant (pour US seulement): COSTES, Vincent [FR/FR]; 19, rue Emile Littré, F-31850 Montrabe (FR).
- (74) Mandataires: MARTIN, Jean-Jacques etc.; Cabinet Regimbeau, 26, avenue Kléber, F-75116 Paris (FR).
- (81) États désignés (national): IN, JP, US
- (84) États désignés (régional): brevet européen (AT. BE. CH, CY, DE, DK, ES. FI. FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

[Suite sur la page suivante]


- (54) Title: DEVICE FOR ACQUIRING STEREOSCOPIC IMAGES
- (54) Titre: DISPOSITIF POUR L'ACQUISITION D'IMAGES STEREOSCOPIQUES




- (57) Abstract: The invention concerns a device for acquiring stereoscopic images comprising a primary mirror (1) or a near-parabolic mirror, a secondary mirror (2) located on the primary mirror optical axis between said primary mirror and its focal point, tertiary reflecting means (4a, 4b, 5a, 5b, 7a, 7b, 8) arranged relative to the primary mirror on the side opposite the secondary mirror reflecting along two directions different from that of the primary mirror optical axis the optical beams received by the primary mirror along two specific directions of incidence, the primary mirror being capable of being traversed by the tertiary beams, said tertiary reflecting means comprising means for focusing the optical beams which they receive along said two directions onto image acquisition means.
- (57) Abrégé: Dispositif pour l'acquisition d'images stéréoscopiques qui comporte un miroir primaire (1) ou proche de la parabole, un miroir secondaire (2) situé sur l'axe optique du miroir primaire entre ledit miroir primaire et son foyer, des moyens de réflexion tertiaires (4a, 4b, 5a, 5b, 7a, 7b, 8) qui sont disposés par rapport au miroir primaire du côté opposé au miroir secondaire, le miroir secondaire réfléchissant selon deux directions distinctes de celle de l'axe optique du miroir primaire les faisceaux optiques qui sont reçus par le miroir primaire selon deux directions d'incidence données, le miroir primaire étant apte à être traversé par les faisceaux optiques ainsi réfléchis pour leur permettre d'atteindre les moyens de réflexion tertiaires, lesdits moyens de réflexion tertiaires comportant des moyens pour focaliser les faisceaux optiques qu'ils reçoivent selon ces deux directions sur des moyens d'acquisition d'images.



1/3




2/3





TO THE REAL PROPERTY OF THE PARTY.

3/3



FIG_3





Attorney Docket No. 3401–4035

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

DEVICE FOR ACQUIRING STEREOSCOPIC IMAGES

the specification of which O is attached and/or was filed on SEPTEMBER 8, 2000 as United States Application Serial No.

or PCT International Application No. PCT/FR00/02486 and was amended on

(if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56.

1 hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate or § 365(a) of any PCT International application(s) designating at least one country other than the United States, listed below and have also identified below, any foreign application(s) for patent or inventor's certificate, or any PCT International application(s) having a filing date before that of the application(s) of which priority is claimed:

-	Country	Application Number	Date of Filing	Priority Clair	ned Under 35 U.S.C. 119
	FRANCE	99/11355	10 SEPTEMBER 1999	X YES	0 NO
				O YES	O NO

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below:

Application Number	Date of Filing
1	1

I hereby claim the benefit under 35 U.S.C. § 120 of any United States applications) or § 365(c) of any PCT International applications) designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application(s) in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application(s) and the national or PCT International filing date of this application:

Application Number	Date of Filing	Status (Patented, Pending , Abandoned)
PCT/FR00/02486	08 SEPTEMBER 2000	Pending

I hereby appoint the following attorney and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office

John C. Vassil (Reg. No. 19,098), Alfred P. Ewert (Reg. No. 19,887), David H. Pfeffer (Reg. No. 19,825), Harry C. Marcus (Reg. No. 22,390), Robert E. Paulson (Reg. o. 21,046), Stephen R. Smith (Reg. No. 22,615), Kurt E. Richter (Reg. No. 24,052), J. Robert Dailey (Reg. No. 27,434), Eugene Moroz (Reg. No. 25,237), John F. Sweeney (Reg. No. 27,471), Arnold 1. Rady (Reg. No. 26,601), Christopher A. Hughes (Reg. No. 26,914), William S. Feiler (Reg. No. 26,728), Joseph A. Calvaruso (Reg. No. 28,287), James W. Gould (Reg. No. 28,859), Richard C. Komson (Reg. No. 27,913), Israel Blum (Reg. No. 26,710), Bartholomew Verdirame (Reg. No. 28,483), Maria C.H. Lin (Reg. No. 29,323), Joseph A. DeGirolamo (Reg. No. 28,595), Michael P. Dougherty (Reg. No. 32,730), Seth J. Atlas (Reg. No. 32,454), Andrew M. Riddles (Reg. No. 31,657), Bruce D. DeRenzi (Reg. No. 33,676), Mark J. Abate (Reg. No. 32,527), John T. Gallagher (Reg. No. 35,516), Steven F. Meyer (Reg. No. 35,613) and Kenneth H. Sonnenfeld (Reg. No. 33,285), Tony V. Pezzano (Reg. No. 36,813) of Morgan & Finnegan, E.L.P. whose address is: 345 Park Avenue, New York, New York, 10154; and Michael S. Marcus (Reg. No. 31,727), and John E. Hoel (Reg. No. 26,279), of MORGAN & FINNEGAN L.L.P. whose address is: 1775 Eye Street, Suite 400, Washington, D.C. 20006—

My attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Address all communications to MORGAN & FINNEGAN, 345 Park Avenue, New York, New York, 10154 (Phone: 212 758-4800) (Fax: 212 751-6849)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full Name of First Inventor Vincent COSTES	Inventor's Signature Date March 11, 2002
Residence MONTRABE, FRANCE	Citizenship French
HA HA	
Post Office Address 19 rue Emile Littré, 31850 MONTRAB	E, FRANCE

Listing of Inventors Continued on Page 2 hereof. O Yes

8 No